

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 08-088115
(43)Date of publication of application : 02.04.1996

(51)Int.Cl. H01F 3/08
B22F 3/12
B22F 3/24
H01F 41/02


(21)Application number : 06-223623 (71)Applicant : MITSUBISHI MATERIALS CORP
(22)Date of filing : 19.09.1994 (72)Inventor : UCHIYAMA KAZUO

(54) YOKE

(57)Abstract:

PURPOSE: To prevent a gap in the surface part of a sintered body from being clogging because no machining is performed and to form an effective tri-iron tetroxide film by a steam treatment in a yoke which is manufactured by powder metallurgy.

CONSTITUTION: A yoke 1 as a magnetic product has a shape in which one end of an outer circumferential tube part 2 and one end of an inner circumferential tube part 3 are connected by a ringed edge part 4. When the yoke 1 is manufactured, a raw-material powder is compressed, a green compact is molded, and the green compact is then heated and sintered. After that, steaming is executed to a sintered body without executing any machining.



LEGAL STATUS

- [Date of request for examination]
- [Date of sending the examiner's decision of rejection]
- [Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]
- [Date of final disposal for application]
- [Patent number]
- [Date of registration]
- [Number of appeal against examiner's decision of rejection]
- [Date of requesting appeal against examiner's decision of rejection]
- [Date of extinction of right]